

# Cromartie Top Loading Kilns



Exclusively manufactured for Cromartie by  **SKUTT**

MODEL	PHASE	NOMINAL VOLTS	TOTAL AMPS	WATTS	ORTON CONE	TEMP °c	CAPACITY	OPENING	CHAMBER DEPTH	GROSS WT
<b>GlazeTech</b>	<b>1</b>	<b>230</b>	<b>13</b>	<b>3000</b>	<b>8+</b>	<b>1200+</b>	<b>30L</b>	<b>36cm</b>	<b>23cm</b>	<b>59 kg</b>
GlazeTech	1	230	16	3600	10	1300	1.1	14"	9"	130 lbs
<b>KM714</b>	<b>1</b>	<b>230</b>	<b>13</b>	<b>3000</b>	<b>8+</b>	<b>1200+</b>	<b>40L</b>	<b>36cm</b>	<b>34cm</b>	<b>50 kg</b>
KM714	1	230	16	3600	10	1300	1.4	14"	13"	110 lbs
<b>KM818</b>	<b>1</b>	<b>230</b>	<b>29</b>	<b>6670</b>	<b>10</b>	<b>1300</b>	<b>70L</b>	<b>45cm</b>	<b>46cm</b>	<b>66 kg</b>
KM818					10	1300	2.6	18"	18"	145 lbs
<b>KM822</b>	<b>1</b>	<b>230</b>	<b>35</b>	<b>8050</b>	<b>10</b>	<b>1300</b>	<b>90L</b>	<b>45cm</b>	<b>57cm</b>	<b>78 kg</b>
KM822					10	1300	3.2	18"	22"	170 lbs
<b>KM827</b>	<b>1</b>	<b>230</b>	<b>38</b>	<b>8740</b>	<b>10</b>	<b>1300</b>	<b>110L</b>	<b>45cm</b>	<b>68cm</b>	<b>96 kg</b>
KM827	3 & N	3 x 230			10	1300	3.8	18"	27"	211 lbs
<b>KM1018</b>	<b>1</b>	<b>230</b>	<b>40</b>	<b>9200</b>	<b>10</b>	<b>1300</b>	<b>130L</b>	<b>60cm</b>	<b>46cm</b>	<b>114 kg</b>
KM1018	2 & N	2 x 230	40	9200	10	1300	4.6	24"	18"	250 lbs
<b>KM1022</b>	<b>1</b>	<b>230</b>	<b>50</b>	<b>11500</b>	<b>10</b>	<b>1300</b>	<b>160L</b>	<b>60cm</b>	<b>57cm</b>	<b>123 kg</b>
KM1022	3 & N	3 x 230	50	11500	10	1300	5.7	24"	22"	271 lbs
<b>KM1027</b>	<b>1</b>	<b>230</b>	<b>50</b>	<b>11500</b>	<b>10</b>	<b>1300</b>	<b>200L</b>	<b>60cm</b>	<b>68cm</b>	<b>132 kg</b>
KM1027	3 & N	3 x 230	50	11500	10	1300	7.0	24"	27"	290 lbs
<b>KM1218</b>	<b>1</b>	<b>230</b>	<b>50</b>	<b>10560</b>	<b>10</b>	<b>1300</b>	<b>185L</b>	<b>72cm</b>	<b>46cm</b>	<b>150 kg</b>
KM1218	2 & N	2 x 230	50	10560	10	1300	6.6	28"	18"	330 lbs
<b>KM1222</b>	<b>1</b>	<b>230</b>	<b>50</b>	<b>11500</b>	<b>10</b>	<b>1300</b>	<b>230L</b>	<b>72cm</b>	<b>57cm</b>	<b>164 kg</b>
KM1222	3 & N	3 x 230	50	11500	10	1300	8.1	28"	22"	360 lbs
<b>KM1227</b>	<b>1</b>	<b>230</b>	<b>60</b>	<b>12250</b>	<b>10</b>	<b>1300</b>	<b>280L</b>	<b>72cm</b>	<b>68cm</b>	<b>186 kg</b>
KM1227	3 & N	3 x 230	60	12250	10	1300	9.9	28"	27"	410 lbs
<b>KM1231</b>	<b>1</b>	<b>230</b>	<b>72</b>	<b>17300</b>	<b>10</b>	<b>1300</b>	<b>328L</b>	<b>72cm</b>	<b>79cm</b>	<b>205 kg</b>
KM1231	3 & N	3 x 230	72	17300	10	1300	11.6	28"	31"	450 lbs
<b>KM1627</b>	<b>*3</b>	<b>400</b>	<b>40 per phase</b>	<b>23600</b>	<b>10</b>	<b>1300</b>	<b>524L</b>	<b>117cm</b>	<b>68cm</b>	<b>244 kg</b>
KM1627	*3	400	40 per phase	23600	10	1300	18.5	46"	27"	535 lbs

\*3 phase – cross phase connection only on this model

Find us on





Providing quality and value since 1946

## TOP LOADING KILNS FROM CROMARTIE

In brief:-

- Solid construction
- Site virtually anywhere due to modular construction
- Conservatively rated Kanthal A1 elements and wiring
- Mains cable to kiln included (over 3 metres chargeable)
- Commando Plug optional (recommended for easy safe maintenance)
- Health and Safety "best practice" Captive key interlock fitted as standard
- Includes double relay system for additional security
- \*KilnMaster (up to 64 segments!) fitted as standard
- Includes spare thermocouple
- Reversible lid coated to eliminate dust and debris
- Lid lifter standard on 10 and 12 sided models
- Two position lid brace
- Easily maintained
- 24 month warranty (excludes elements)

KilnMaster provides for all cone number firings and has an additional 12 storable user definable programs that can be programmed in ramp dwell mode up to 64 segments can be provided by linking two programs. This heavily featured programme provides:-

- Troubleshooting error codes and procedures
- Controlled cooling in cone mode
- Cone correlation in ramp/hold mode
- Type S or K thermocouple settings
- Maximum temperature setting to prevent accidental over fires
- Double key press start
- Current sensing allows for monitoring electrical costs
- Track the number of firings
- KilnLink ready track your kilns performance on the Internet – anywhere!

Delivery - We can deliver "kerbside" or into position according to customers' requirements. In most cases we can arrange for full electrical connection, commissioning and operational training at the time of delivery. Delivery charges on this basis will be quoted separately and according to the specific requirements and circumstances.

**Top loading kilns are typically in stock and immediately available**

**Please call us with any queries on 01782 319435**