

Cromartie Top Loading Kilns



Exclusively manufactured for Cromartie by  **SKUTT**

MODEL	PHASE	NOMINAL VOLTS	TOTAL AMPS	WATTS	ORTON CONE	TEMP °c	CAPACITY	OPENING	CHAMBER DEPTH	GROSS WT
GlazeTech	1	230	13	3000	8+	1200+	31L	37cm	23cm	59 kg
GlazeTech	1	230	16	3600	10	1300	1.1	14.5"	9"	130 lbs
KM714	1	230	13	3000	8+	1200+	40L	36cm	36cm	50 kg
KM714	1	230	16	3600	10	1300	1.4	14.38"	13.5"	110 lbs
KM818	1	230	29	6670	10	1300	73L	44.45cm	45.72cm	66 kg
KM818					10	1300	2.6	17.5"	18"	145 lbs
KM822	1	230	35	8050	10	1300	90L	44.45cm	55.88cm	78 kg
KM822					10	1300	3.2	17.5"	22"	170 lbs
KM827	1	230	38	8740	10	1300	107L	44.45cm	68.58cm	96 kg
KM827	3 & N	3 x 230			10	1300	3.8	17.5"	27"	211 lbs
KM1018	1	230	40	9200	10	1300	129L	59.38cm	45.72cm	114 kg
KM1018	2 & N	2 x 230	40	9200	10	1300	4.6	23.38"	18"	250 lbs
KM1022	1	230	50	11500	10	1300	160L	59.38cm	55.88cm	123 kg
KM1022	3 & N	3 x 230	50	11500	10	1300	5.7	23.38"	22"	271 lbs
KM1027	1	230	50	11500	10	1300	196L	59.38cm	68.58cm	132 kg
KM1027	3 & N	3 x 230	50	11500	10	1300	7.0	23.38"	27"	290 lbs
KM1218	1	230	50	10560	10	1300	185L	71.45cm	45.72cm	150 kg
KM1218	2 & N	2 x 230	50	10560	10	1300	6.6	28.13"	18"	330 lbs
KM1222	1	230	50	11500	10	1300	227L	71.45cm	55.88cm	164 kg
KM1222	3 & N	3 x 230	50	11500	10	1300	8.1	28.13"	22"	360 lbs
KM1227	1	230	60	12250	10	1300	277L	71.45cm	68.58cm	186 kg
KM1227	3 & N	3 x 230	60	12250	10	1300	9.9	28.13"	27"	410 lbs
KM1231	1	230	72	17300	10	1300	325L	71.45cm	78.74cm	205 kg
KM1231	3 & N	3 x 230	72	17300	10	1300	11.6	28.13"	31"	450 lbs
KM1627	*3	400	40 per phase	23600	10	1300	518L	117.84x78.1cm	68.58cm	244 kg
KM1627	*3	400	40 per phase	23600	10	1300	18.5	46x30.75"	27"	535 lbs

*3 phase – cross phase connection only on this model

Find us on





Providing quality and value since 1946

TOP LOADING KILNS FROM CROMARTIE

In brief:-

- Solid construction
- Site virtually anywhere due to modular construction
- Conservatively rated Kanthal A1 elements and wiring
- Mains cable to kiln included (over 3 metres chargeable)
- Commando Plug optional (recommended for easy safe maintenance)
- Health and Safety "best practice" Captive key interlock fitted as standard
- Includes double relay system for additional security
- *KilnMaster (up to 64 segments!) fitted as standard
- Includes spare thermocouple
- Reversible lid coated to eliminate dust and debris
- Lid lifter standard on 10 and 12 sided models
- Two position lid brace
- Easily maintained
- 24 month warranty (excludes elements)

KilnMaster provides for all cone number firings and has an additional 12 storable user definable programs that can be programmed in ramp dwell mode up to 64 segments can be provided by linking two programs. This heavily featured programme provides:-

- Troubleshooting error codes and procedures
- Controlled cooling in cone mode
- Cone correlation in ramp/hold mode
- Type S or K thermocouple settings
- Maximum temperature setting to prevent accidental over fires
- Double key press start
- Current sensing allows for monitoring electrical costs
- Track the number of firings
- KilnLink ready track your kilns performance on the Internet – anywhere!

Delivery - We can deliver "kerbside" or into position according to customers' requirements. In most cases we can arrange for full electrical connection, commissioning and operational training at the time of delivery. Delivery charges on this basis will be quoted separately and according to the specific requirements and circumstances.

Top loading kilns are typically in stock and immediately available

Please call us with any queries on 01782 319435